



Main

Range	Actassi
Product	Equipped sliding 19" data panel
Equipment level	Basic
Provided equipment	2 quick fix 19" mountings 24 RJ45 connectors
Footprint	Slim
Rack unit	1U
Number of ports	24 ports STP
Performance	6
Additional features	Automatic grounding

Complementary

Material	DC01 1.2 mm for metal sheet PA6 for plastic part PA66 GF20 for plastic part
Colour	Dark grey RAL 7016
Width	490 mm
Height	47 mm
Depth	240 mm
Weight	2.5 kg

Environment

Standards	IEC 60297 ISO/IEC 11801 ed. 2.2, 2011 NF C 20-150
Temperature range	-10...55 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0852 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.