



Datenblatt - Fiche technique - Data sheet

14.01.3590



ROLINE DisplayPort Video-Splitter, 2fach

ROLINE Distributeur DisplayPort, double

ROLINE DisplayPort Splitter, 2-way

Item no.: 14.01.3590

ROLINE DisplayPort Splitter, 2 ports, black color



Features:

- Supports DisplayPort specification V1.2a
- Supports one dual mode input port and two dual mode output ports
- Resolution support up to 4K2K@60Hz
- Supports 5.4Gbit/s per lane (4 lanes at 21.6Gbps) bandwidth.
- Supports audio up to PCM 7.1(32-192kHz Fs sample rate)
- Video Timing:
 - * 4K2K 60 Hz: 24 bits/pixel in DP 1.2a configuration
 - * 1920 x 1080 (FHD) 240 Hz, 24 bits/pixel
 - * All 3D formats defined in DP 1.2a and HDMI standards
- Audio Timing:
 - * All audio formats as specified in DP 1.2a and HDMI standards
 - * SPDIF; 2-Ch LPCM, AC3, DTS, bit depth up to 24 bits, sample rate up to 192 kHz
- Supports full 3D
- Supports SST & MST
- Case material: metal

Specifications:

Input port	1 x DisplayPort
Output ports	2 x DisplayPort(dual mode)
Power Supply	DC 5V2A
Operating Temperature	0°C~40°C / 32°F ~ 104°F
Storage temperature	-20°C~60°C / -4°F ~ 140°F
Relative Humidity	20~90% RH (non-condensing)