

Terminales DIN 46234



Material: Cobre
Acabado: Estantado

Ref.	Sección cable mm²	Dimensiones mm.								Ref.	Sección cable mm²	Dimensiones mm.							
		Ød2	Ød3	l	a	c	d1					Ød2	Ød3	l	a	c	d1		
D-2.2-0.5	0.2-0.5	2.2	5.0	10.0	4.0	2.0	1.0	1.000		D-4-6	2.5-6	4.3	8.0	14.0	6.0	6.0	3.6	1.000	
D-2.7-0.5		2.7	5.0	10.0	4.0	2.0	1.0			D-5-6		5.3	10.0	15.0	6.0	6.0	3.6		
D-3.2-0.5		3.2	5.0	10.0	4.0	2.0	1.0			D-6-6		6.5	11.0	16.0	6.0	6.0	3.6		
D-3.7-0.5		3.7	6.0	12.0	4.0	2.0	1.0			D-8-6		8.4	14.0	19.0	6.0	6.0	3.6		
D-4.3-0.5		4.3	6.5	12.0	4.0	2.0	1.0			D-10-6		10.5	18.0	21.0	6.0	6.0	3.6	500	
D-5.3-0.5		5.3	8.0	12.0	4.0	2.0	1.0			D-12-6		13.0	18.0	21.0	6.0	6.0	3.6		
D-2.2-1	0.5-1.5	2.2	6.0	11.0	5.0	4.0	1.6	1.000		D-5-10	10	5.3	10.0	16.0	8.0	8.0	4.5	500	
D-2.7-1		2.7	6.0	11.0	5.0	4.0	1.6			D-6-10		6.5	11.0	17.0	8.0	8.0	4.5		
D-3.2-1		3.2	6.0	11.0	5.0	4.0	1.6			D-8-10		8.4	14.0	20.0	8.0	8.0	4.5		
D-3.7-1		3.7	6.0	11.0	5.0	4.0	1.6			D-10-10		10.5	18.0	21.0	8.0	8.0	4.5		
D-4.3-7-1		4.3	7.0	11.5	5.0	4.0	1.6			D-12-10		13.0	22.0	23.0	8.0	8.0	4.5		
D-4.3-1		4.3	8.0	12.0	5.0	4.0	1.6			D-5-16	16	5.3	11.0	20.0	10.0	10.5	5.8	500	
D-5.3-8-1		5.3	8.0	12.5	5.0	4.0	1.6			D-6-16		6.5	11.0	20.0	10.0	10.5	5.8		
D-5.3-1		5.3	10.0	13.0	5.0	4.0	1.6			D-8-16		8.4	14.0	22.0	10.0	10.5	5.8		
D-6.5-10-1		6.5	10.0	13.0	5.0	4.0	1.6			D-10-16		10.5	18.0	24.0	10.0	10.5	5.8		
D-6.5-1		6.5	11.0	15.0	5.0	4.0	1.6			D-12-16		13.0	22.0	26.0	10.0	10.5	5.8	250	
D-8.4-1		8.4	14.0	17.0	5.0	4.0	1.6			D-5-25	25	5.3	12.0	25.0	11.0	12.0	7.5	50	
D-10.5-14-1		10.5	14.0	17.0	5.0	4.0	1.6			D-6-25		6.5	12.0	25.0	11.0	12.0	7.5		
D-10.5-18-1		10.5	18.0	19.0	5.0	4.0	1.6			D-8-25		8.4	16.0	25.0	11.0	12.0	7.5		
D-3.2-2.5	1.5-2.5	3.2	6.0	11.0	5.0	4.5	2.3	1.000		D-10-25		10.5	18.0	26.0	11.0	12.0	7.5		
D-3.7-2.5		3.7	6.0	11.0	5.0	4.5	2.3			D-12-25		13.0	22.0	31.0	11.0	12.0	7.5		
D-4.3-6.8-2.5		4.3	6.8	11.6	5.0	4.5	2.3			D-16-25		17.0	28.0	35.0	11.0	12.0	7.5		
D-4.3-2.5		4.3	8.0	12.0	5.0	4.5	2.3			D-6-35	35	6.5	15.0	26.0	12.0	15.0	9.0	50	
D-5.3-8.0-2.5		5.3	8.0	13.5	5.0	4.5	2.3			D-8-35		8.4	16.0	26.0	12.0	15.0	9.0		
D-5.3-2.5		5.3	10.0	14.0	5.0	4.5	2.3			D-10-35		10.5	18.0	27.0	12.0	15.0	9.0		
D-6.5-2.5		6.5	11.0	16.0	5.0	4.5	2.3			D-12-35		13.0	22.0	31.0	12.0	15.0	9.0		
D-8.4-2.5		8.4	14.0	17.0	5.0	4.5	2.3			D-16-35		17.0	28.0	36.0	12.0	15.0	9.0		
D-10.5-15-2.5		10.5	15.0	17.0	5.0	4.5	2.3			D-6-50	50	6.5	18.0	34.0	16.0	17.0	11.0	50	
D-10.5-18-2.5		10.5	18.0	18.5	5.0	4.5	2.3			D-8-50		8.4	18.0	34.0	16.0	17.0	11.0		
D-13.0-2.5		13.0	18.0	20.0	5.0	4.5	2.3			D-10-50		10.5	18.0	34.0	16.0	17.0	11.0		
										D-12-50		13.0	22.0	36.0	16.0	17.0	11.0		
										D-16-50		17.0	28.0	40.0	16.0	17.0	11.0		