



MICRO BNC JACK TO JACK ADAPTOR TRUE 75 Ohm

67-500-D126



images for illustration purposes only



3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BERYLLIUM COPPER	GOLD
1	BODY	BRASS	GOLD
ITEM	DESCRIPTION	MATERIAL	PLATING

A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES		
REVISION : C00		NAME	SIGNATURE	DATE
ISSUE : 1		DRAWN G.E.		16/11/2015
		CHK'D I.G.		16/11/2015
		APPV'D		
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE		

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 55

Electrical Specification

Impedance: 75 Ohm

Frequency: 0-12 GHz

Dielectric W/V: 1000 Veff

Insulation res: 1000 M-Ohm

Mechanical Specification

Contact Retention: 15 N min

Cable Retention: Not Applicable

Mating cycles: 500

Weight: 1.87 g

Connector Interface

image for illustration purposes only

