


Terminales redondos para tornillo

NYLON



Material aislante: Poliamida (NYLON)

Voltaje y temperatura máximos de uso: 600V - 105°C

Ref.	Sección mm ² /AWG	Medidas (mm)						
		d2	B	L	F	D	E	
EF-05022	0.10-0.50	2.20	5.00	16.50	6.00	2.30	8.00	100/1000
EF-05027	26-22	2.70	5.00	16.50	6.00			
EF-05032		3.20	5.00	16.50	6.00			
EF-05037		3.70	6.00	19.00	8.00			
EF-05043		4.30	6.50	19.25	8.00			
EF-05053		5.30	8.00	20.00	8.00			
EF-15032	0.25-1.65	3.20	5.50	17.50	4.30	4.10	10.50	100/1000
EF-15037	22-16	3.70	5.50	17.50	4.30			
EF-15037-1		3.70	6.60	20.40	6.60			
EF-15043		4.30	6.60	20.40	6.60			
EF-15043-1		4.30	8.00	21.80	7.30			
EF-15053		5.30	8.00	21.80	7.30			
EF-15064		6.40	11.60	27.50	11.20			
EF-15084		8.40	11.60	27.50	11.20			
EF-15105		10.50	13.70	31.50	14.20			
EF-15130		13.00	19.60	36.40	16.00			
EF-25032	1.04-2.63	3.20	6.60	20.60	6.30	4.50	11.00	100/1000
EF-25032-1	16-14	3.20	8.50	23.00	7.80			
EF-25037		3.70	6.60	20.60	6.30			
EF-25037-1		3.70	8.50	23.00	7.80			
EF-25043		4.30	6.60	20.60	6.30			
EF-25043-1		4.30	8.50	23.00	7.80			
EF-25053		5.30	8.50	23.00	7.80			
EF-25053-1		5.30	9.50	22.90	7.30			
EF-25064		6.40	12.00	28.00	11.00			
EF-25084		8.40	12.00	28.00	11.00			
EF-25105		10.50	13.60	31.70	13.90			
EF-25130		13.00	19.20	36.40	16.00			
EF-55032	2.63-6.64	3.20	9.50	26.70	8.00	6.60	14.00	50/500
EF-55037	12-10	3.70	9.50	26.70	8.00			
EF-55043		4.30	7.40	26.70	8.00			
EF-55043-1		4.30	9.50	26.70	8.00			
EF-55053	2.63-6.64	5.30	9.50	26.70	8.00	6.60	14.00	50/500
EF-55064	12-10	6.40	12.00	32.70	12.70			
EF-55084		8.40	15.00	34.90	13.40			
EF-55105		10.50	15.00	34.90	13.40			
EF-55130		13.00	19.20	39.60	16.00			