



BNC STRAIGHT CRIMP/CRIMP JACK 10-054-B36-FA



Images for illustration purposes only




4	CRIMP SLEEVE	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	PHOS. BRONZE	GOLD
1	BODY	BRASS	NICKEL
ITEM	DESCRIPTION	MATERIAL	PLATING
A4	SHEET 1 OF 1		
REVISION :	A02	DRAWN	IG 06/08/2012
ISSUE :	2	CHK'D	GE 13/08/2012
		APPV'D	
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR			
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE			

Suitable for Cables:

(FA) Belden 1855ENH, Draka 0.6/2.8AF, BD SD01, Image 360

Stripping Dimensions



a = 4.0 mm
b = 8.0 mm
c = 16.0 mm
d = 12.0 mm

* CUT FOIL TO DIM. "b"

Assembly Procedure: AP001

Tooling

Centre Contact: Hex 1.72mm A/F Tool No: 96-HTS-75 or 336A

Crimp Sleeve: Hex 5.41mm A/F Tool No: 96-HTS-75 or 336A

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 64

Electrical Specification

Impedance: 75 Ohm

Frequency: 0 - 4.5 GHz

Dielectric W/V: 1500 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 10 N min


Cable Retention: 150 N min

Mating cycles: 250

Weight: 6.94 g

Connector Interface

Image for illustration purposes only



-28.9 dB @ 1.0 GHz
-22.2 dB @ 2.0 GHz
-22.2 dB @ 3.0 GHz
-17.9 dB @ 4.5 GHz

Return Loss Graph

