


Punteras aisladas - Tipos TE/PD

DIN 46228



Material: Cu-E electro-estañado con aislante de propileno.
Temperatura máxima: +105°C



Ref.	COLOR FRANCÉS	Sección mm2	Medidas (mm)			COLOR DIN	Ref.
			L	F			
TE-0.14	marrón	0.14	10	6	100		--
TE-0.14-L		0.14	12	8			--
TE-0.25	amarillo	0.25	10	6	100	violeta	PD-0.25
TE-0.25-L		0.25	12	8			PD-0.25-L
TE-0.34	verde	0.34	10	6	100	rosa	PD-0.34
TE-0.34-L		0.34	12	8			PD-0.34-L
TE-0.50	blanco	0.50	12	8	100	blanco	PD-0.50
TE-0.50-K		0.50	14	6			PD-0.50-K
TE-0.50-HL		0.50	16	10			PD-0.50-HL
TE-0.75	azul cielo	0.75	12	8	100	gris	PD-0.75
TE-0.75-K		0.75	14	6			PD-0.75-K
TE-0.75-HL		0.75	16	10			PD-0.75-HL
TE-0.75-L		0.75	18	12			PD-0.75-L
TE-1.00	rojo	1.00	12	8	100	rojo	PD-1.00
TE-1.00-K		1.00	14	6			PD-1.00-K
TE-1.00-HL		1.00	16	10			PD-1.00-HL
TE-1.00-L		1.00	18	12			PD-1.00-L
TE-1.50	negro	1.50	12	8	100	negro	PD-1.50
TE-1.50-K		1.50	14	6			PD-1.50-K
TE-1.50-HL		1.50	16	10			PD-1.50-HL
TE-1.50-HLS		1.50	18	12			PD-1.50-HLS
TE-1.50-L		1.50	24	18			PD-1.50-L
TE-2.50	gris	2.50	14	8	100	azul	PD-2.50
TE-2.50-HL		2.50	18	12			PD-2.50-HL
TE-2.50-L		2.50	24	18			PD-2.50-L
TE-4.00	naranja	4.00	17	10	100	gris	PD-4.00
TE-4.00-HL		4.00	20	12			PD-4.00-HL
TE-4.00-L		4.00	26	18			PD-4.00-L
TE-6.00	verde	6.00	20	12	100	amarillo	PD-6.00
TE-6.00-L		6.00	26	18			PD-6.00-L
TE-10.00	marrón	10.00	22	12	100	rojo	PD-10.00
TE-10.00-L		10.00	28	18			PD-10.00-L