


MICRO BNC INSULATED BULKHEAD JACK TO JACK ADAPTOR TRUE 75 Ohm

Ref. 67503D126



Images for illustration purposes only



5	OUTER BODY	BRASS	NICKEL
4	NUT	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BERYLLIUM COPPER	GOLD
1	BODY	BRASS	GOLD

ITEM	DESCRIPTION	MATERIAL	PLATING
------	-------------	----------	---------

A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES	
----	--------------	-------------------------------	--

REVISION:	D00	NAME	SIGNATURE	DATE
-----------	-----	------	-----------	------

ISSUE:	1	DRAWN	G.E.	14/11/2015
--------	---	-------	------	------------


		CHE'D	I.G.	14/11/2015
--	--	-------	------	------------

		APP'D		
--	--	-------	--	--

6-8 COLNE ROAD,
TWICKENHAM,
MIDDLESEX.
TW1 4JR

THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS
SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL
GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT
TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR
NOTICE.

Recommended Mounting:



Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 40

Electrical Specification

Impedance: 75 Ohm

Frequency: 0-12 GHz

Dielectric W/V: 1000 Veff

Insulation res: 1000 M-Ohm

Mechanical Specification

Contact Retention: 15 N min

Cable Retention: Not Applicable

Mating cycles: 500

Weight: 3.09 g

Connector Interface

Image for illustration purposes only

