


Cableados y Conexiones S.L.

BNC STRAIGHT JACK TO JACK ADAPTOR (12GHz)

Ref. 10500W126



Images for illustration purposes only



3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BERYLLIUM COPPER	GOLD
1	BODY	BRASS	GOLD
ITEM	DESCRIPTION	MATERIAL	PLATING
A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES	
REVISION : A00		NAME	SIGNATURE
ISSUE : 1		DATE	
6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX. TW1 4JR		DRAWN	IG
		CHK'D	GE
		APPV'D	
THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE			

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 64

Electrical Specification

Impedance: 75 Ohm

Frequency: 0-18 GHz

Dielectric W/V: 1500 Veff

Insulation res: 5000 M-Ohm

Mechanical Specification

Contact Retention: 150 N min

Cable Retention: N/A

Mating cycles: 500

Weight: 8.00 g

Connector Interface

Image for illustration purposes only



Performance

-28.24 dB @ 3.0 GHz

-23.20 dB @ 6.0 GHz

-25.33 dB @ 9.0 GHz

-32.06 dB @ 12.0 GHz

-18.64 dB @ 18.0 GHz

Return Loss Graph

