


MICRO BNC STRAIGHT CRIMP / CRIMP PLUG ref. 67005B66EF1




Images for illustration purposes only



Suitable for Cables:

(EF) Belden 1855A

Stripping Dimensions



a = 4.0 mm
b = 8.0 mm
c = 16.0 mm
d = 12.0 mm

* CUT FOIL TO DIM. "b"

Assembly Procedure: AP001

Tooling

Centre Contact: SQ 0.042 inch or 1.07mm A/F Tool No: 96-HTS-77

Crimp Sleeve: Hex 0.178 inch or 4.52mm A/F Tool No: 96-HTS-77

Alignment Tool: Not Applicable Extraction: 96-1132

Environmental Specification

Operating Temp: -55 to +155 Deg C.

IP Rating (Mated): IP 64

Electrical Specification

Impedance: 75 Ohm

Frequency: 0-12 GHz

Dielectric W/V: 1000 Veff

Insulation res: 10000 M-Ohm

Mechanical Specification

Contact Retention: 10 N min

Cable Retention: 150 N min

Mating cycles: 500

Weight: 5.10 g

Connector Interface

Image for illustration purposes only



7	SPRING	SS	N/A
6	COUPLING NUT	BRASS	NICKEL
5	GASKET	SILICONE	N/A
4	CRIMP SLEEVE	BRASS	NICKEL
3	INSULATOR	PTFE	N/A
2	CENTRE CONTACT	BeCu	GOLD
1	BODY	BRASS	NICKEL

ITEM	DESCRIPTION	MATERIAL	PLATING
------	-------------	----------	---------

A4	SHEET 1 OF 1	DIMENSIONS ARE IN MILLIMETRES	
----	--------------	-------------------------------	--

REVISION :	A07	NAME	SIGNATURE	DATE
------------	-----	------	-----------	------

ISSUE :	1	DRAWN	GE	16/04/2012
---------	---	-------	----	------------

		CHK'D	IG	16/04/2012
--	--	-------	----	------------

		APPV'D		
--	--	--------	--	--

6-8 COLNE ROAD, TWICKENHAM, MIDDLESEX, TW1 4JR

THE INFORMATION IS GIVEN AS AN INDICATION ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IN THE CONTINUAL GOAL TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO MAKE ANY MODIFICATIONS NECESSARY WITHOUT PRIOR NOTICE.