





## Zeichnung/Drawing



## PIN-Belegung/PIN out



## Querschnitt/Cross section



## Cat 6 Netzwerkkabel

### Mechanik

- Anschlüsse: 2x RJ45-Stecker
- Kontakte: 8P8C; vergoldet
- Knickschutzhülle: angespritzt; mit Längenangabe
- Innenleiter: 4x2xAWG 24/7
- Isolierung: PVC
- Farbkodierung: EIA/TIA 568B
- Schirmung: U/UTP

### Leistung

- Datenstandard: CAT 6 (250 MHz), 1GBase-T, 155/622-MBit-ATM

### Elektrik

- Spannungsfestigkeit: DC 300 V
- Kontaktwiderstand: max. 3  $\Omega$
- Isolationswiderstand: 10 M $\Omega$  @ 10 ms
- Impedanz: 100  $\Omega$

### Umwelt

- RoHS-konform

## Cat 6 Network cable

### Mechanical

- Connectors: 2x RJ45 plug
- Contacts: 8P8C; gold-plated
- Strain relief: molded; with length indication
- Inner conductor: 4x2xAWG 24/7
- Insulation: PVC
- Color coding: EIA/TIA 568B
- Shielding: U/UTP

### Power

- Data standard: CAT 6 (250 MHz), 1GBase-T, 155/622-MBit-ATM

### Electrical

- Withstanding voltage: DC 300 V
- Contact resistance: max. 3  $\Omega$
- Insulation resistance: 10 M $\Omega$  @ 10 ms
- Impedance: 100  $\Omega$

### Environmental

- RoHS compliant

