

Cableados y Conexiones S.L.

CABLE VIDEO 1.0/4.8 NEGRO UHD FRNC (LSZH) VK7 4K

Ref. 1048NG-LSZH

4K-UHD 6G-SDI

BROADCASTING VIDEO CABLE DIGITAL 6 Gb/s UHDTV - 3 Gb/s HD-SDI COMPLIANCE IEC 60754-1 IEC 60754-2 IEC 61034-2			Class CPR E_{ca}	CATEGORY A+ EN 50117
--	--	--	---------------------------------	-----------------------------------

CU ø 1,00 mm	PEG ø 4,60 mm	LTA ø 4,70 mm	CS ø 5,20 mm	LSZH ø 6,95 mm
-----------------	------------------	------------------	-----------------	-------------------



MECHANICAL DATA

A	INNER CONDUCT.	PLAIN COPPER	ø 1,00 mm
B	DIELECTRIC	GAS INJECTED SKIN-FOAM-SKIN POLYETHYLENE	ø 4,60 ± 0,10 mm
C	SHIELD	ALUMINIUM + POLYESTER + ALUMINIUM TAPE - COVERAGE	h. 18 mm 100%
D	BRAID	TINNED COPPER - COVERAGE	192 x 0,12 mm 96%
E	SHEATH	FLAME RETARDANT NON-CORROSIVE THERMOPLASTIC FREE OF HALOGENS	ø 6,95 ± 0,10 mm

- COLOUR	JET BLACK RAL 9005 RED LILAC RAL 4001	PASTEL TURQUOISE RAL 6034 TURQUOISE BLUE RAL 5018
- PRINTING	## METER ##	HD PRO CABLE 75 OHM LSZH CE 56 WEEK/YEAR EN 50575:2014 + A1:2016 Eca

MINIMUM BENDING RADIUS (mm)

- SINGLE	ø EXTERNAL X 5
- REPEATED	ø EXTERNAL X 10
TEMPERATURE RANGE	-40 °C / +80 °C

CABLE WEIGHT (Kg/Km)

- COPPER	28,1
- PLASTIC	32,8
- TOTAL	62,6

ELECTRICAL PROPERTIES at 20°C

IMPEDANCE	75 ± 3 Ohm	RESISTANCE	
CAPACITANCE	53 pF/m	- INNER CONDUCT.	22,5 Ohm/Km
VELOCITY RATIO	84%	- BRAID	8,3 Ohm/Km
		TENSION	
		- SHEATH	4,5 kV
		SPARK TESTING	

ATTENUATIONS dB/100 m.

5 MHz	1,5	135 MHz	6,9	750 MHz	17,2	2500 MHz	34,1
71,5 MHz	5,1	180 MHz	8,3	1000 MHz	20,5	3000 MHz	38,2
88,5 MHz	5,6	360 MHz	11,7	1500 MHz	25,6	6000 MHz	57,8

MAXIMUM TRANSMISSION DISTANCE CALCULATED - meters

SMPTE ST 259				SMPTE ST 292	SMPTE ST 424	SMPTE ST		
143 Mb/s	177 Mb/s	270 Mb/s	360 Mb/s	1,5 Gb/s	3,0 Gb/s	425-4	2081-1	2082-1
Composite NTSC	Composite PAL	Comp. 4:3 SD-SDI	Widescreen 16:9 SD-SDI	HD-SDI 1080i 1,5G-SDI	HD-SDI 1080p 3G-SDI	3,0 Gb/s	6,0 Gb/s	12,0 Gb/s
588	536	435	361	116	78	UHDTV1 UHDTV2		
						156	105	69

STRUCTURAL RETURN LOSS dB

30 ÷ 470 MHz	>29	3000 ÷ 4500 MHz	>20
470 ÷ 862 MHz	>27	4500 ÷ 6000 MHz	>15
862 ÷ 2150 MHz	>24	6000 ÷ 12000 MHz	-
2150 ÷ 3000 MHz	>21		

SCREENING EFFECTIVENESS dB EN 50117 STANDARD

5 ÷ 30 MHz	<5	mOhm/m
30 ÷ 1000 MHz	>95	dB
1000 ÷ 2000 MHz	>90	dB
2000 ÷ 3000 MHz	>80	dB

The producer reserves himself to make modification on the item without any notice.

Caycon

© 2026 Cableados y Conexiones S.L.
C/ Ciudad de Frías nº25 Nave 8 28021 Madrid ESPAÑA (Spain)
Tfno: 91 428 00 36 - 91 471 54 32
info@caycon.es <http://www.caycon.es>